




Sensata
Technologies



KLIXON | 3NT SERIES

Fixed Temperature Thermostats

WORLD CLASS PERFORMANCE

The 3NT is an automatic reset thermostat designed to meet customer specific application requirements. With its unique dry seal, the switch is protected from environmental hazards such as water, dust, oil, etc. without the use of epoxies or additives. The 3NT is UL/CSA, KEMA/ENEC approved.

Sensata Technologies has been a leading global supplier of pressure sensors & switches for over 50 years.

Key Features

- Automatic Reset
- Small and easy to mount
- Fast thermal response
- Innovative dry seal design - protects from moisture and dust
- Reliable 100K cycle life
- High temperature - to 275°F (135°C)

General Description

The 3NT thermostat from Sensata Technologies is a new, custom built, automatic reset thermostat designed to meet your specific application requirements. Its patented, tamperproof, Klixon® snap-acting bimetal disc provides reliable, repeatable switch actuation, for electrical loads ranging from dry circuits to 10A @ 240Vac.

The dry seal also allows direct integration of the thermostat into a wire harness, eliminating extra connections.

The core of the 3NT is the proven 1NT thermostat. Recognized by all major worldwide agencies, hundreds of millions are used daily in a wide variety of appliance, HVAC, automotive, and specialty applications. Manufactured since 1981, the 1NT thermostat is produced at ISO 9000 certified manufacturing sites.

Applications

Small size, a variety of mounting options, and outstanding thermal response, makes the 3NT an excellent temperature control for dehumidifiers, freezers, heat pumps, ice makers, refrigerators, or any place where a fixed temperature control is required in a wet or dirty environment.



Application Shown:
Residential heat pump

Design Specifications

Operating Temperature:

-20 to 135°C (-4 to 275°F)

Ambient Temperature:

-40°C to maximum wire lead insulation temperature rating:

PVC - 105°C

XLP - 125°C

(Allow 15°C de-rating below wire insulation rating at maximum 10A current)

Minimum Nominal

Temperature Differential:

8°C (15°F)

Dielectric Strength:

750 Vrms

1500 Vrms terminals to case

Switch Configurations

Switch Configurations

3NT thermostats are SPST switches which typically reset automatically. Single operation function is available.

Sensata recommends standard silver contacts for most applications. Customers may prefer to specify gold contacts for low voltage (<12V) or low current (less than 100mA) applications. Min. 25 m Amp

Standard Wire Leads:

18 AWG (1/32" or 1/16" wall thickness 105°C PVC)

16 AWG (1/32" thick, 105°C, PVC insulation)

1/32" wall thickness 125°C XLP insulation available upon request

A wide variety of wire lead terminals are available from stock. Custom termination support is available.

Agency Approvals

	File Number	Category
UL (USA) ¹	SA995	Category SDFY2
UL (CANADA) ¹	SA995	Category SDFY8
KEMA (ENEC)	2014531.16	EN 60730-2-9

1) Recognized to US and Canadian requirements by Underwriters Laboratories (UL873 and C22.2 No. 24)

Electrical Ratings

Agency	Cycles x1000	Volts	FLA	LRA	Amps (resistive)	VA
UL (USA, Canada)	100	120 Vac	5.8	34.8	10	125
	100	240 Vac	2.9	17.4	10	125
	30	120 Vac	10.0	40.0		
	30	240 Vac	10.0	40.0		
	100	30 Vdc			1	
ENEC (Europe)	30	240 Vac			16	

Standard Temperatures and Tolerances

Nominal Top Temperature		Nominal Differential		Open Temperature Tolerance		Close Temperature Tolerance	
°F	°C	°F	°C	°F	°C	°F	°C
32 to 80	0 to 27	20 - 29	11 - 16	±5.5	±3	±7.5	±4
		30 - 38	17 - 21	±5.5	±3	±8.5	±4.5
		50 - 60	22 - 33	±5.5	±3	±10	±5.5
81 to 167	28 to 75	20 - 23	11 - 13	±5.5	±3	±7.5	±4
		24 - 29	14 - 16	±5.5	±3	±8.5	±4.5
		30 - 59	17 - 33	±5.5	±3	±10	±5
*168 to 199	*76 to 93	20 - 23	11 - 13	±5.5	±3	±7.5	±4
		24 - 29	14 - 16	±5.5	±3	±8.5	±4.5
		30 - 59	17 - 33	±5.5	±3	±9	±5
*200 to 249	*94 to 121	20 - 29	11 - 16	±6.5	±3.5	±8.5	±4
		30 - 38	17 - 21	±6.5	±3.5	±10	±4.5
		39 - 59	22 - 33	±6.5	±3.5	±12	±6.5
		50 - 99	34 - 55	±10	±5.5	±20	±11
250 to 275	122 to 135	24 - 38	14 - 21	±7.5	±4	±10	±5.5
		39 - 59	22 - 33	±7.5	±4	±14.5	±8
		60 - 99	34 - 55	±10	±5.5	±20	±11

*Minimum bottom temperature of 50°C (122°F)

Numbering System

Part Number

3NT	01	L	H	XXXX
Sensata P/N Series	Contact Material	Switch Opening Logic	Dry Seal Construction	ID Number
	01 - Silver 11 - Gold	L - On Temp. Rise F - On Temp. fall	H - High Temp. (Silicon rubber) N - No leads	Customer & Application Specific

Temperature Code

L	50	F	30
Switch Type	Operating Temperature	Temp. Code	Differential
L - Limit F - Fan	Nominal Opening Temperature	C - Celsius F - Fahrenheit	Difference between Nominal Open and Nominal Close Temperature

Typical Physical Characteristics Dimensions in mm (inches)

<p>Basic 3NT Dimensions</p>	<p>Surface Mount Clip</p>	<p>Surface Mount Clip</p>
<p>Locking Tube Mount Clip (ø3/8) Shown</p> <p>Additional Clips Available for [ø1/4], [ø5/16], [ø1/2], [ø5/8] Tubes</p>	<p>Open Tube Mount Clip (ø3/8) Shown at 90° CCW Rotation 90° and 180° CW Rotations Available</p> <p>Additional Clips Available for [ø1/2], [ø5/8] Tubes</p>	<p>Snap Tube Mount Clip For (ø5/16) and (ø3/8) Tubes</p>


Ordering Samples

Sensata encourages the use of engineering test samples to assist in your thermostat specification process. Please call or FAX the following information for the fastest possible sampling lead times:

1. Customer product application
2. Electrical load requirements: voltage, current, power factor (inductive loads)
3. Nominal setpoint temperatures (opening and closing)
4. Maximum allowable temperature setpoint tolerances (see table for standards)
5. Mounting style desired:
 - flat surface - screw hole or snap-in
 - tube - diameter and orientation
6. Cup material (aluminum or copper)
7. Lead wire specifications (length, wire gage, terminations, insulation type and thickness)
8. Estimated annual usage

Non-functional thermocouple samples are available to determine thermostat setpoints. Please specify thermocouple type (J,K,T) and length. Standard wire size is 30 gauge.

3NT Dry Seal Design



Important Notice: The 3NT is not hermetically sealed, and should not be submerged in liquid. For such applications, please contact Sensata Technologies for advice.



The World Depends on Sensors and Controls

Sensata Technologies

529 Pleasant Street, MS B19
Attleboro, MA 02703-2964
Phone: (508) 236-1894
(508) 236-3192

Fax: 508-236-2349
www.sensata.com

Important Notice: Sensata Technologies (Sensata) reserves the right to make changes to or discontinue any product or service identified in this publication without notice. Sensata advises its customers to obtain the latest version of the relevant information to verify, before placing any orders, that the information being relied upon is current. Sensata assumes no responsibility for infringement of patents or rights of others based on Sensata applications assistance or product specifications since Sensata does not possess full access concerning the use or application of customers' products. Sensata also assumes no responsibility for customers' product designs.