



SILICONE HV 0,6/1 Kv (red copper)



Date reviewed : 23/02/2011

Revision Number: 4

Silicone cables

Single core flexible red copper cable with silicone rubber sheath type EI2, VDE certified.

Technical data

Voltage U ₀ / U	600/1000 V
Normative references	VDE 0250 TEIL 502
Applications / Terms of use	Resistance to heath, for class H networking, lighting, high tension circuitry.
Type electric conductor	Flexible red copper
Type of insulation	EI2
Sheath color	On demand (one or two colours)
Operating temperature	-60° C +130° C
Test voltage	5000 V
Cable marking	ELETTRO BRESCIA Reg. No. 7875

SILICONE HV 0,6/1 Kv (red copper)

Technical data

Section (mm ²)	Diameter capillary (mm)	Wire size (mm)	Average thickness of insulation (mm)	Maximum outside diameter (mm)	Electrical resistance (M Ω -km a 20°C)	Factor cu (kg/km)
1x0,50	0,20	0,90	1,0	3,0	39,0000	4,80
1x0,75	0,20	1,10	1,0	3,2	26,0000	7,20
1x1,00	0,20	1,20	1,0	3,3	19,5000	9,60
1x1,50	0,25	1,50	1,0	3,6	13,3000	14,40
1x2,50	0,25	1,90	1,2	4,4	7,9800	24,00