



Rocker switches



SX83 Series

Square cut out - 30X22
ENEC electrical rating up to 20A




- Soft and flat push-buttons available
- Switch with signal light version available
- PVC cover available

Products

Customising on demand

Accessories


Electrical features

ENEC electrical rating up to	20A
Electro-mechanical cycles number up to	50.000
Room temperature up to	125 °C
Flammability	UL 94 V2
Heat and fire resistance	GWFI 850 °C GWIT 750 °C on demand
Contact gap	≥ 3 mm
Approvals available (to check according to the rating of each single material code)	  
Reference standards	EN 61058 UL 1054

Wiring diagrams

- Double single-pole switch
- Illuminated double single-pole switch
- Illuminated single-pole switch + pilot light
- Single-pole double two-way switch

Cut out (mm)



	FRAME SIZE			L	K	J
	H	X	Y			
STANDARD	2	32	25	FRAME 30 ^{+0,2}	22 ^{+0,1}	0,7-3,5
PVC CAP VERSION	2	32	25	RES. 30,2 ^{+0,2}	22 ^{+0,1}	0,7-2,5
SPECIAL FRAME	2,5	31,5	23,5	29,4 ^{+0,2}	22 ^{+0,1}	0,7-3,5
UK CUT OUT	2	30,2	25	28,2 ^{+0,1}	22,3 ^{+0,1}	0,7-3,5

Stampa scheda