

SOLAR CABLES

The manufacturer reserve the right to modify the products at any time without prior notice.



Elettrobrescia S.p.a.
Via Bulloni, 36 Camignone di Passirano (BS)
Phone: +39 0306850663
E-mail: info@elettrobrescia.it
www.elettrobrescia.it



H1Z2Z2-K

Low smoke halogen-free, flexible, single-core power cables with cross-linked insulation and sheath.

TECHNICAL DATA

Nominal voltage	1,0/1,0 kVca - 1,5 kVdc
Applications/Usage conditions	The single core H1Z2Z2-K cable represents a right solution to link the solar cellars between them or to wire with frequency converters and terminal boards. The H1Z2Z2-K cable guarantees good resistance to UV-rays and various weather conditions. The wide working temperature range allows the use also in extreme conditions, avoiding deterioration caused by heat and permitting a right use of the fotovoltaic panel in every season.
Conductor	Flexible tinned copper
Insulation type	Compound conforming to EN 50618
Sheath type	Compound conforming to EN 50618
Sheath colour	Black, blue, red
Operating temperatures	-40°C +90°C
Short circuit temperature	Max 250°C 5 sec
Test voltage	6500 Vac - 15000 Vdc
Cable markings	ELETTRO BRESCIA H1Z2Z2-K (I/II)* 1xsect. mm² TÜV Rheinland Reg. Nr. R (60109330/60108022)* Dca-s2, d2, a1 max 1,8KVdc
Minimum bending radius	4 times the cable diameter for fixed and mobile laying.
Notes	* Markings depending on raw materials. 16 mm² version only for H1Z2Z2-K I.

STANDARD REFERENCE

Main standard	EN 50618
UV Resistance	EN 50618
Conductor	EN 60228; IEC 60228
Self-Extinguishing	EN 60332-1-2; IEC 60332-1-2
Ozone resistance	EN 50396 8.1.3

CERTIFICATIONS



DIMENSIONS

Cross section	Wires max diameter	Conductor diameter	Core thickness	Core diameter	Sheath thickness	Medium outer diameter	Electrical resistance at 20°C	Cable approx. weight	Cu factor
(Nxmm ²)	(mm)	(mm)	(mm)	(mm) ± 0,1	(mm)	(mm) ± 0,2	(Ω/km)	(kg/km)	(kg/km)
1x2,50	0,250	N/A	0,75	3,50	0,80	5,1	8,2100	47,00	24,00
1x4,00	0,300	N/A	0,72	3,80	0,80	5,4	5,0900	58,00	38,40
1x6,00	0,300	N/A	0,74	4,40	0,80	6,0	3,3900	78,00	57,60
1x10,00	0,400	N/A	0,73	5,40	0,80	7,0	1,9500	125,00	96,00
1x16,00	0,400	N/A	0,75	6,40	0,90	8,2	1,2400	184,00	153,60

Please refer to the standard series EN 50565 as guide to use for cables with a rated voltage not exceeding 450/750 V (U/U) and CEI 20-92 as guide for the handling and warehousing of wooden drums for electric cables.



Elettro Brescia, was founded in 1983 and during these years it has become a dynamic and technologically advanced company which nowadays holds its successful position among the best manufacturers of electric cables.

Our company, harmoniously situated in the wonderful countryside of Franciacorta, covers an area of 15.000 qm, including a production division, a warehouse and the research and analysis laboratory.

The complete automation of the production process assures consistency of quality and an absolute safety.

The compliance with the latest European regulations is a spur to all of us for a steady close control of the quality of the product. In these years we directed our energies to follow our mission: "To serve the markets worldwide with the best pre and aftersale service, good quality and very competitive prices".