





FV70

**Pillar Terminal Block
with wire protector
(5 poles; must be fixed
on an insulated surface)**



TECHNICAL DATA

	IEC Standards	American Standards
Ratings	450V - 41A	300V - 15A
Wire size	6.0 sqmm	18 + 14AWG
Working Temperature	- 5 ÷ 150°C (short time 180°C)	23 ÷ 239°F
Plastic Material	Polyamide PA6.6 glass filled brown colour, UL94 V0, GWT 960°C	
Metal Parts	Cage insert made in nickel plated brass; M4 Captive screw made in zinc plated steel; Wire protector made in stainless steel	
Marking	1 - 2 - 3 - 4 - 5	
Accessories		

Approvals	File Nr.	Ratings (sqmm/AWG - V - A - T)	Standard References
	E 5431	6.0 sqmm - 450V - 41A - 150°C	EN 60998-1; EN 60998-2-1
	121170	4.0 (flexible) / 6.0 (rigid) sqmm - - 450V - 41A - 150°C	DIN EN 60998-1; DIN EN 60998-2-1 (VDE 0613)

PACKAGING

Type	P-N	Pack.	Dim. Pack. (LxHxP)	Weight (Kg)
FV 70 WP/5P	109275	250	30x20x40	10.5

DIMENSIONAL
DRAWING

