





PA107

**Cable clamp.
For snap-in fixing on chassis**



TECHNICAL DATA

	IEC Standards			American Standards	
	A	B	C	D	E
Dimensions mm (inches)	26 (1.02)	23 (0.91)	29 (1.14)	2.5 (0.10)	0.6 + 2 (0.02) (0.08)
Wire size	3 x 0.75 sqmm ÷ 3 x 1.5 sqmm (max. cable Ø 10 mm)			3 x 20 AWG ÷ 3 x 16 AWG (max. cable Ø 0.4")	
Working Temperature	- 5 ÷ 125°C (short time 155°C)			23 ÷ 221°F	
Plastic Material	Polyamide PA6 black colour, UL94 V2, GWT 850°C				
Cable Clamp Screw	3.5 x 15 mm (0.14" x 0.60") HI-LO				

Approvals	File Nr.	Ratings (sqmm/AWG – V – A – T)	Standard References
	E 6562	Gr. 10mm - 3x0.75 sqmm / 3x1.5 sqmm – 125°C	EN 60598-1 /A1; /A12; /A13; EN 60335-1
	LR 40455	accessory, strain relief	CSA C22-2 N.158-1987; E.C.N 584B

PACKAGING				
Type	P-N	Pack.	Dim. Pack. (LxHxP)	Weight (Kg)
PA 107	970590	3000	40x39x40	18.5

DIMENSIONAL
DRAWING

