







PA220

**Pillar Terminal Block
(12 poles)**



TECHNICAL DATA

	IEC Standards	American Standards
Ratings	750V - 76A	300V - 80A
Wire size	16.0 sqmm ²	18 ÷ 6 AWG
Working Temperature	- 5 ÷ 110°C (short time 140°C)	23 ÷ 221°F
Plastic Material	Polyamide PA6.6 natural colour, UL94 V2, GWT 960°C	
Metal Parts	Cage insert made in nickel plated brass; M5 Captive screw made in zinc plated steel	
Accessories	PA52	

Approvals	File Nr.	Ratings (sqmm/AWG – V – A – T)	Standard References
	CA 02.00594	16.0 sqmm - 750V – 76A – 110°C	EN 60998-1; EN 60998-2-1
	121155	16.0 sqmm (rigid) 10.0 sqmm (flexible) – 750V - 76A – 110°C	DIN EN 60998-1; DIN EN 60998-1/A1; DIN EN 60998-2-1 (VDE 0613)
	E76048 vol. 1 sec. 8	18 ÷ 6 AWG - 300V - 80A - 105°C	UL 1059; CSA C22-2 N.158-1987
	LR 40455	18 ÷ 6 AWG - 600V - 75A	CSA C22-2 N.158-1987; E.C.N 584B

PACKAGING

Type	P-N	Pack.	Dim. Pack. (LxHxP)	Weight (Kg)
PA 220/12P	104712	50*	30x20x40	9.5

*M.O.Q. (Minimum Q.ty Order): 5.000 pieces

DIMENSIONAL
DRAWING

